

Apollo Advantage™ Bathing System Specifications

Minimum Room Size: 72 in (182.9 cm) wide by 114 in (289.6 cm) long **Space Saver** 72 in (182.9 cm) wide by 102 in (259.1 cm) long

Dimensions:	Length	Width	Height (All)
Tub:	71 in (180.3 cm)	34 in (86.5 cm)	36 in (91.4 cm) Side of Tub
Space Saver:	59 in (149.8 cm)	34 in (86.5 cm)	50 in (127.0 cm) at Control Panel Top
Cabinet:	17 in (43.2 cm) Deep	56 in (142.2 cm)	81 in (205.7 cm) Max installed (Reservoir)
Level Glide™ Carrier:	32.5 in (82.5 cm)	23.75 in (60.3cm)	40 in (101.6 cm)

Installed Length: Door Closed: 71 in (180.3 cm) Door Open: 102 in (259.1 cm)

Space Saver: Door Closed: 59 in (149.8 cm) Door Open: 90 in (228.6 cm)

Component Weight: Tub 289 lb (131 kg) Cabinet 183 lb (83 kg)
 Level Glide™ without Scale 83 lb (38 kg) Level Glide™ with Scale 118 lb (53.5 kg)

Total Shipping Weight: 845 lb (384 kg)

Installation Time: 1.5 Hours

Inspection & Adjustments: 1 Hour

Reservoir Capacity: Maximum of 65 gal (247 L)

Water Supply: Requires two (2) 0.75 in (1.9 cm) garden hose thread (GHT) wall mounted faucets.
 Minimum of 30 PSI (2.1 Bar) for hot and cold required.

Water Connection: Provided with two (2) 60 in (152.4 cm) high pressure stainless steel hoses with 0.75 in (1.9 cm) GHT ends.

Waste: 2 in (5.1 cm) PVC schedule 40 pipe. Outside diameter 2.4 in (6.1 cm)

Electrical: Dedicated 115 VAC plug-in receptacle protected by a 15A GFCI circuit breaker (not supplied).

Tub Fill: RADA Thermoscopic mixing valve; ASSE 1016 certified.

Shower: Hand held with 84 in (213.4 cm) ANSI A112.18.1 hose and ASSE 1014 Vacuum Breaker

Tub Entry: Door with 24.5 in (62.2 cm) opening where residents are transferred into tub.

Gaskets: Dual gaskets extruded from EDPM Neoprene.

Whirlpool Models

Whirlpool Pump Motor: 1.5 HP; 13A; 115 VAC; 60HZ; 3400 RPM; 125 GPM at 10 PSI head pressure.

Whirlpool Control: Pneumatic pushbutton switch.

Whirlpool Jets: Four whirlpool jets with adjustable nozzles.

Whirlpool Water Requirement: 54 gal (205 L) (Space Saver 47 gal or 178 L) minimum required to run whirlpool jets without resident.

Air Spa Models

Air Spa Blower Motor: 900 W variable speed, thermally protected blower motor with 300W ceramic heating element, 120 VAC; 11A; 60 HZ.

Air Spa Control: Multifunction, low voltage DC electronic keypad

Air Spa Jets: 20 total air jets (16 on Space Saver), 2 seat jets with 6 lateral openings each and 18 vertical jets (14 on Space Saver) with 24 openings each.

Air Spa Water Requirement: None

Level Glide™ Transfer System

Carrier: Heavy duty stainless steel.

Casters: Four heavy-duty, medical grade, stainless steel ball bearing swivel casters with 4 in (10 cm) non-marring wheels.
 Two of the casters have toe released brakes.

Chair: Stainless steel frame with plastic contoured seat and back.

Safety Straps: 2 safety straps.

Capacity: 400 lb (181 kg)

Safety Locks: Chair single lock to release chair from track stops. Dual secondary locks that release during transfer into tub.

***Specifications subject to change**